

ROBUST AND FLEXIBLE -

THE GATE FOR LARGE OPENINGS







ADVANTAGES AT A GLANCE

Opening speed up to 2.0 m/s

Door size up to 12.000 mm x 8.500 mm

Resistance to wind load up to class 3


Extremely robust

Choice of three colors

Permanent curtain tension

Weight compensation by tension springs

SPECIAL FEATURES



ROBUST AND FLEXIBLE

The fast-running roller door with a 3 mm thick fabric curtain is vertical running, fast-opening and fast-closing.

The permanent tensioning of the curtain ensures safe and smooth door operation.


Hinged rail boxes allow easy cleaning and maintenance even with large amounts of dust.


The Transrapid withstands wind loads up to class 3 due to the integrated internal spring steel wind pressure safety devices with ball-bearing double-pair track rollers.

Thus, the Transrapid is also suitable as an external door.









Bale cladding

Wind pressure protection

Weight compensation and permanent curtain tension

TECHNICAL DATA

- Opening speed up to 2.0 m/s
- Closing speed up to 0.8 m/s
- Door sizes up to 12,000 mm height and 8.500 mm width
- DR2100 microprocessor control system with main switch and integrated frequency converter
- 230 V/50Hz, IP54 operator
- Required lintel height min. 580 mm

SAFETY

- Access protection by means of all-round cladding
- Drive-through monitoring by means of light barrier and safety contact strip
- Emergency opening by means of pull cable with break release or reel chain
- Signal lights and traffic light control (optional)

OUR FURTHER PRODUCT RANGE



SPIRAL DOORS



VERTIKAL HIGH-SPEED DOORS



MACHINE PROTECTION DOORS



FOLDING DOORS



SWING DOORS



SECTIONAL DOORS



HORIZONTAL HIGH-SPEED DOORS



STRIP CURTAINS



```
STEEL / ALUMINUM ROLLER DOORS
```

SCOPE OF APPLICATION



ITW Industrietore GmbH Adolf-Kolping-Straße 14 73072 Donzdorf Germany Tel. +49 7162 9129-60 Fax +49 7162 9129-64 info@itw-torsysteme.de www.itw-torsysteme.de

