

THE HIGH SPEED DOOR WITH

CURTAIN TENSIONING AND WEIGHT COMPENSATION







ADVANTAGES AT A GLANCE



Opening speed up to 2.0 m/s



Door size up to 6.0 m x 6.0 m



Resistance to wind load up to class 3



Low lintel requirement



Permanent curtain tension



Weight compensation



Wide range of colors



Atex




V2A



Deep-freeze

SPECIAL FEATURES



CURTAIN TENSION AND WEIGHT COMPENSATION

The Transspeed can be used for additional hall closure or as an interior door. The Transspeed is a high-quality solution for any building opening that is passed through very frequently by forklifts or floor vehicles.


Different curtain designs can be used to meet a wide range of requirements.

The permanent curtain tensioning system keeps the door leaf under tension at all times during opening and closing.


The tension spring system for weight compensation rounds off the system and offers fast emergency opening.








Anti-Crash-System



Counterbalance and Curtain tension



Light grid



Bale and drive cover

TECHNICAL DATA

- Opening speed up to 2.0 m/s
- Closing speed up to 0.8 m/s
- Door sizes up to 6.0 m height and 6.0 m width
- DR2100 microprocessor control system with main switch and integrated frequency converter
- 230 V/50Hz, IP54 Operator
- Required lintel height min. 447 mm
- Curtain available in various colors or fully printed with a motif of your choice

SAFETY

- Access protection by means of all-round cladding
- Passage monitoring by means of contactless light grid
- Anti-crash function automatic reset (optional)
- Emergency opening by pull rope, automatic opening in case of power failure (optional)
- Signal lights and traffic light control (optional)



SPIRAL DOORS



FOLDING DOORS



HORIZONTAL HIGH-SPEED DOORS



VERTIKAL HIGH-SPEED DOORS



SWING DOORS



STRIP CURTAINS



MACHINE PROTECTION DOORS



SECTIONAL DOORS



STEEL / ALUMINUM ROLLER DOORS

SCOPE OF APPLICATION





















INDUSTRY

TRANSPORT

LOGISTICS

AUTOMOTIVE M. PROTECTIONS CLEAN ROOM SUPERMARKET

FOOD

COOLING AREA

ATEX

ITW Industrietore GmbH Adolf-Kolping-Straße 14 73072 Donzdorf

Germany

Tel. +49 7162 9129-60 Fax +49 7162 9129-64 info@itw-torsysteme.de www.itw-torsysteme.de

